

Flat Parallel Submersible Pump Cable

Construction:

Annealed bare stranded copper conductors insulated with PVC in a flat parallel construction to form a 75°C 600 Volt Multi-Conductor Submersible Pump Cable. UL Listed per UL 83 Type THW as Deep Well Submersible Pump Cable.

Gauge	Stranding	Insulation Thickness	Nom. OD Min. Maj.	Std Package	Shipping Weight ~LB/1000'
14/2 with GND	7/.0242"	0.045"	0.166" X 0.588"	500 or 1000	77
14/3 with GND	7/.0242"	0.045"	0.166" X 0.769"	500 or 1000	92
12/2 with GND	7/.0305"	0.045"	0.190" X 0.610"	500 or 1000	104
12/3 with GND	7/.0305"	0.045"	0.190" X 0.815"	500 or 1000	139
10/2 with GND	7/.0385"	0.045"	0.215" X 0.685"	500 or 1000	151
10/3 with GND	7/.0385"	0.045"	0.210" X 0.910"	500 or 1000	195
8/2 with #10 GND	19/.0295" – 7/.0385"	0.060"	0.285" X 0.885"	500 or 1000	201
8/3 with #10 GND	19/.0295" – 7/.0385"	0.060"	0.273" X 1.225"	500 or 1000	283
6/3 with #8 GND	19/.0372" – 19/.0295"	0.060"	0.320" X 1.357"	500 or 1000	428
4/3 with #8 GND	19/.0469" – 19/.0295"	0.060"	0.370" X 1.550"	500 or 1000	637

- Special packaging is available upon request.
- Resistant to acid, abrasion, alkalis, flame, gas, and oil.
- Cable is sequentially marked.

MADE IN THE USA

Rev 2 10-8-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926