

## HD Jacketed Submersible Pump Cable

### Construction:

Annealed bare stranded copper conductors PVC insulated and run parallel with a PVC black jacket to form a 75°C 600 Volt Multi-Conductor Submersible Pump Cable. UL Listed per UL 83 Type THW as Deep Well Submersible Pump Cable.

Gauge	Stranding	Insulation Thickness	Jacket Thickness	Nom. OD Min. X Maj.	Std Package	Shipping Weight ~LB/1000'
14/2 with GND	19/.0147"	0.045"	0.045"	0.262" X 0.594"	500 / 1000	110
14/3 with GND	19/.0147"	0.045"	0.045"	0.262" X 0.762"	500 / 1000	136
12/2 with GND	19/.0185"	0.045"	0.045"	0.271" X 0.680"	500 / 1000	143
12/3 with GND	19/.0185"	0.045"	0.045"	0.275" X 0.840"	500 / 1000	187
10/2 with GND	19/.0234"	0.045"	0.045"	0.314" X 0.754"	500 / 1000	200
10/3 with GND	19/.0234"	0.045"	0.045"	0.314" X 0.988"	500 / 1000	267
8/3 with #10 GND	19/.0295"(8ga) – 19/.0234"(10ga)	0.060"	0.050"	0.375" X 1.135"	500 / 1000	394
6/3 with #8 GND	19/.0372"(6ga) – 19/.0295"(8ga)	0.060"	0.050"	0.410" X 1.320"	500 / 1000	560
4/3 with #8 GND	19/.0469"(4ga) – 19/.0295"(8ga)	0.060"	0.050"	0.468" X 1.465"	500 / 1000	744
2/3 with #6 GND	19/.0591"(2ga) – 19/.0372"(6ga)	0.060"	0.065"	0.564" X 1.731"	500 / 1000	1072

- Special packaging is available upon request.
- Resistant to acid, abrasion, alkalis, flame, gas, and oil.
- Cable is sequentially marked

MADE IN THE USA

Rev 2 10-8-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

**Kalas Manufacturing, Inc.**

25 Main St., P.O. Box 328,

Denver, PA 17517

**E-MAIL** [info@kalaswire.com](mailto:info@kalaswire.com)

**P** 717 336 5575 **F** 717 335 1926