

## Ice Blue Jacketed Submersible Pump

### Construction:

Annealed bare stranded copper conductors run parallel with TPE insulation and blue jacket to form a 90°C Dry 75°C Wet 600 Volt Multi-Conductor Submersible Pump Cable. UL Listed as Deep Well Submersible Pump Cable.

Gauge	Stranding	Insulation Thickness	Jacket Thickness	Nom. OD Min. X Maj.	Std Package	Shipping Weight ~LB/1000'
12/2 with GND	65/.010"	0.030"	0.030"	0.225" X 0.528"	500 or 1000	93
12/3 with GND	65/.010"	0.030"	0.030"	0.224" X 0.692"	500 or 1000	121
10/2 with GND	105/.010"	0.030"	0.030"	0.265" X .0610"	500 or 1000	137
10/3 with GND	105/.010"	0.030"	0.030"	0.250" X 0.796"	500 or 1000	188
8/3 with #10 GND	19/.0295" – 19/.0234"	0.045" (8ga) 0.030" (10 ga)	0.040"	0.330" X 0.987"	500 or 1000	287

- Special packaging is available upon request.
- Oil Resistant.
- Low Temperature -65°C.
- Cable is sequentially marked.

MADE IN THE USA

Rev 1 10-08-09

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

**Kalas Manufacturing, Inc.**

25 Main St., P.O. Box 328,

Denver, PA 17517

**E-MAIL** [info@kalaswire.com](mailto:info@kalaswire.com)

**P** 717 336 5575 **F** 717 335 1926