

EPDM WELDING CABLE

Construction:

Highly flexible stranded No. 30 bare copper conductor insulated with high grade EPDM. A paper separator is utilized to enhance stripability. Maximum conductor operating temperature is 105°C in circuits not exceeding 600 volts. Minimum temperature rating -50°C.

Size	Stranding	Insulation Thickness	Nom O.D.	Std. Package	Shipping Weight ~lbs / 1000 feet
6	259/.010"	0.060"	0.320"	1000	113
4	378/.010"	0.060"	0.376"	1000	157
2	636/.010"	0.060"	0.430"	500	244
1	780/.010"	0.080"	0.510"	500	315
1/0	1007/.010"	0.080"	0.560"	500	389
2/0	1254/.010"	0.080"	0.600"	500	475
3/0	1596/.010"	0.080"	0.655"	500	591
4/0	2014/.010"	0.080"	0.720"	500	734

- Special packaging is available upon request.

MADE IN THE USA

Rev 02 10-19-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926