

Construction:

SAE GPT Primary Wire 60V DC is constructed with flexible stranded copper conductors. Insulation is 105°C PVC. Kalas GPT Primary Wire is constructed to meet the requirements of SAE J1128.

Gauge	Stranding	Insulation Thickness	Nom. OD	Std Package Reel or Drum	Shipping Weight ~LB/1000'
20	7/.0126"	0.023"	0.084"	12000 / 50000	6.3
18	16/.010"	0.023"	0.094"	6000 / 50000	8.5
16	19/.0112"	0.023"	0.103"	5000 / 30000	11
14	19/.0140"	0.023"	0.117"	4000 / 25000	16
12	19/.0177"	0.026"	0.142"	2500 / 18000	25
10	19/.0223"	0.031"	0.176"	1500 / 12000	39
8	19/.0281"	0.037"	0.216"	1000 / 8000	60

- Special stranding and packaging are available upon request.
- Resistant to acid, abrasion, alkalis, coolant, diesel fuel, ethanol, flame, gas, ozone, power steering fluid, oil and transmission fluid.

TWP and HDT are available upon request.

MADE IN THE USA

Rev 02 10-12-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926