

Multi-conductor Golf Course Sprinkler Wire

Construction:

Solid copper conductors insulated with water resistant PVC, twisted, and then jacketed with a liner low density polyethylene to form a durable multiconductor golf course sprinkler system wire. Temperature rating is 75°C to -65°C 600 Volts. Available with U L labeling and print.

Size	Solid Strand Size	Insulation Thickness	Jacket Thickness	Jacketed Nominal O.D.	Std. Package	Shipping Weight ~lbs / 1000 feet
18/2	.0412"	0.015"	0.025"	0.185"	500 & 1000	20
18/3	.0412"	0.015"	0.025"	0.205"	500 & 1000	28
18/4	.0412"	0.015"	0.025"	0.230"	500 & 1000	36
18/5	.0412"	0.015"	0.025"	0.255"	500 & 1000	44
18/6	.0412"	0.015"	0.025"	0.260"	500 & 1000	51
18/7	.0412"	0.015"	0.025"	0.275"	500 & 1000	59
18/8	.0412"	0.015"	0.025"	0.290"	500 & 1000	67
18/9	.0412"	0.015"	0.025"	0.322"	500 & 1000	75
18/10	.0412"	0.015"	0.025"	0.320"	500 & 1000	83
18/12	.0412"	0.015"	0.025"	0.359"	500 & 1000	98
18/13	.0412"	0.015"	0.025"	0.370"	500 & 1000	105

- Direct Burial
- Sunlight Resistant
- Sequentially marked footage
- Features a ripcord for easy stripability of jacket

MADE IN THE USA

Rev 01 10-27-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926