

Low Voltage Landscape Lighting Cable

Construction:

Stranded *Bare Copper* conductor insulated with high grade PVC to form a 2 conductor parallel landscape lighting cable. One leg has raised ridges to identify polarity. UL and c(UL) listed. Operating temperature range is 60°C to -25°C. Voltage rating is 150 Volts.

Gauge	Stranding	Insulation Thickness	Nom. OD Major X Minor	Std. Package	Shipping Weight ~LB/1000'
18/2	16/.010"	0.045"	0.290" X 0.145"	500	28
16/2	26/.010"	0.045"	0.320" X 0.160"	500	36
14/2	41/.010"	0.045"	0.350" X 0.175"	500	49
12/2	65/.010"	0.045"	0.390" X 0.195"	500	68
10/2	105/.010"	0.045"	0.440" X 0.220"	500	95
8/2	168/.010"	0.045"	0.575" X 0.285"	500	158

- Special packaging is available upon request.
- Direct Burial
- Sunlight Resistance
- Sequentially numbered printing available

MADE IN THE USA

Rev 1 10-08-09

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926