

Construction:

SAE SGR Battery Cable 60V DC is constructed with flexible stranded copper conductors. Insulation is 105°C EPDM. Kalas SGR Battery Cable is constructed to meet the requirements of SAE J1127.

Gauge	Stranding	Insulation Thickness	Nom. OD	Std Package	Shipping Weight ~LB/1000'
6	37/.0260"	0.060"	0.305"	1000	104
6	7/19/.0137"	0.060"	0.310"	1000	107
4	7/19/.0170"	0.065"	0.375"	1000	153
4	61/.0250"	0.065"	0.350"	1000	160
2	7/19/.0218"	0.065"	0.438"	1000	248
1	7/19/.0243"	0.065"	0.480"	1000	308
1/0	19/7/.0275"	0.065"	0.525"	500	383
2/0	19/7/.0309"	0.065"	0.575"	500	470
3/0	19/84/.010"	0.078"	0.641"	500	631
4/0	19/106/.010"	0.078"	0.706"	500	766

- Special stranding and packaging are available upon request.
- Resistant to acid, abrasion, alkalis, coolant, diesel fuel, ethanol, flame, gas, ozone, power steering fluid, oil and transmission fluid.

MADE IN THE USA

Rev 02 10-12-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 F 717 335 1926