

Construction:

SAE SXL Primary Wire 60V DC is constructed with flexible stranded copper conductors. Insulation is 125°C XLPE. Kalas SXL Primary Wire is constructed to meet the requirements of SAE J1128.

Gauge	Stranding	Insulation Thickness	Nom. OD	Std Package Reel or Drum	Shipping Weight ~LB/1000'
18	16/.0100"	0.030"	0.108"	5000 / 35000	9.5
16	19/.0112"	0.032"	0.121"	5000 / 25000	13
14	19/.0140"	0.035"	0.139"	3000 / 20000	19
12	19/.0177"	0.037"	0.164"	2000 / 15000	27
10	19/.0223"	0.041"	0.196"	1500 / 10000	41
8	19/.0281"	0.043"	0.224"	1000 / 6000	61

- Special stranding and packaging are available upon request.
- Resistant to acid, abrasion, alkalis, coolant, diesel fuel, ethanol, flame, gas, ozone, power steering fluid, oil and transmission fluid.

MADE IN THE USA

Rev 02 10-12-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926