

UL K-90 WELDING CABLE

Construction:

Highly flexible stranded No. 30 bare copper conductor insulated with high grade PVC / Nitrile Rubber. A separator may be utilized to enhance stripability. Maximum conductor operating temperature is 90°C at 90 Volts . Minimum temperature rating -35°C.

Size	Stranding	Insulation Thickness	Nom O.D.	Std. Package	Shipping Weight ~lbs / 1000 feet
6	7 X 38/.010"	0.080"	0.376"	1000	125
4	7 X 60/.010"	0.080"	0.426"	1000	189
2	7 X 95/.010"	0.085"	0.487"	500	283
1	19 X 44/.010"	0.090"	0.560"	500	357
1/0	19 X 56/.010"	0.090"	0.605"	500	428
2/0	19 X 70/.010"	0.100"	0.665"	500	542
3/0	19 X 88/.010"	0.100"	0.745"	500	661
4/0	19 X 111/.010"	0.105"	0.790"	500	821

- Special stranding and packaging are available upon request.
- Resistant to acid, abrasion, alkalis, coolant, diesel fuel, ethanol, flame, gas, ozone, power steering fluid, oil and transmission fluid.

MADE IN THE USA

Rev 1 10-27-09

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926