

Twisted PVC Submersible Pump Cable

Construction:

Annealed bare solid or stranded copper conductors insulated with PVC and twisted to form a 75°C 600 Volt Multi-Conductor Submersible Pump Cable. UL Listed per UL 83 Type THW as Deep Well Submersible Pump Cable.

Gauge	Stranding	Insulation Thickness	Twisted Nom. OD	Std Package	Shipping Weight ~LB/1000'
14/2 with GND	Solid/.0641"	0.045"	0.339"	500 or 1000	67
14/3 with GND	Solid/.0641"	0.045"	0.380"	500 or 1000	89
12/2 with GND	Solid/.0808"	0.045"	0.369"	500 or 1000	94
12/3 with GND	Solid/.0808"	0.045"	0.414"	500 or 1000	125
10/2 with GND	Solid/.1019"	0.045"	0.421"	500 or 1000	136
10/3 with GND	Solid/.1019"	0.045"	0.472"	500 or 1000	182
8/2 with #10 GND	19/.0295" – solid(.1019")	0.060"	0.538"	500 or 1000	197
8/3 with #10 GND	19/.0295" – solid(.1019")	0.060"	0.608"	500 or 1000	273
6/3 with #8 GND	19/.0372" – 19/.0295"	0.060"	0.728"	500 or 1000	413
4/3 with #8 GND	19/.0469" – 19/.0295"	0.060"	0.819"	500 or 1000	584

- Special packaging is available upon request.
- Resistant to acid, abrasion, alkalis, flame, gas, and oil.

MADE IN THE USA

Rev 2 10-08-09

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926