

EPDM WELDING CABLE

Construction:

Highly flexible stranded No. 30 bare copper conductor insulated with high grade EPDM. A paper separator is utilized to enhance stripability. Maximum conductor operating temperature is 105°C in circuits not exceeding 600 volts. Minimum temperature rating -50°C.

Size	Stranding	Insulation Thickness	Nom O.D.	Std. Package	Shipping Weight ~lbs / 1000 feet
6	259/.010"	0.060"	0.320"	1000	113
4	364/.010"	0.060"	0.348"	1000	147
2	624/.010"	0.060"	0.420"	500	236
1	780/.010"	0.080"	0.503"	500	313
1/0	988/.010"	0.080"	0.533"	500	378
2/0	1235/.010"	0.080"	0.586"	500	463
3/0	1539/.010"	0.080"	0.625"	500	563
4/0	2014/.010"	0.080"	0.720"	500	734

- Special packaging is available upon request.

MADE IN THE USA

Rev 04 4-12-2010

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926