

## 300 Volt PVC & TPE Flexible Cord

### Construction:

Bare or tinned stranded copper conductors insulated with PVC, twisted with or without fillers and jacketed with PVC or TPE to conform to UL and CSA. PVC available 60°C or 105°C. TPE available 90°C or 105°C.

- SJT SJTO SJTOO SJTW SJTOW SJTOOW
- SJE SJEO SJEOO SJEW SJEOW SJEOOW

Size	Stranding	Insulation Thickness	Jacket Thickness	Nom O.D. (With filler)	Nom O.D. (No filler)	Std. Package	Shipping Weight ~lbs / 1000 feet	
							With Filler	Fillerless
18/2*	16/010"	0.030"	0.030"	0.302"	0.287"	5500	36	46
18/3*	16/010"	0.030"	0.030"	0.309"	0.306"	5000	47	55
18/4	16/010"	0.030"	0.030"	0.338"	0.335"	4000	59	68
16/2	26/010"	0.030"	0.030"	0.315"	0.312"	5000	45	58
16/3	26/010"	0.030"	0.030"	0.335"	0.332"	4500	59	70
16/4	26/010"	0.030"	0.030"	0.367"	0.264"	3500	75	87
14/2	41/010"	0.030"	0.030"	0.351"	0.348"	4000	60	77
14/3	41/010"	0.030"	0.030"	0.374"	0.371"	3500	80	95
14/4	41/010"	0.030"	0.030"	0.411"	0.408"	3000	103	119
12/2	65/010"	0.030"	0.045"	0.412"	N/A	2500	89	N/A
12/3	65/010"	0.030"	0.045"	0.437"	N/A	2500	117	N/A
12/4	65/010"	0.030"	0.045"	0.478"	N/A	2000	148	N/A
10/2	104/010"	0.045"	0.045"	0.555"	N/A	1500	153	N/A
10/3	104/010"	0.045"	0.045"	0.589"	N/A	1500	205	N/A
10/4	104/010"	0.045"	0.045"	0.646"	N/A	1000	260	N/A

\*18/2 and 18/3 fillerless enhanced with a micro poly strength member for mechanical strength

- Special stranding and packaging are available upon request.
- Custom constructions available upon request.
- Non-wicking polypropylene, reinforced paper, and jute filler available

**MADE IN THE USA**

Rev 01 06-15-2010

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

**Kalas Manufacturing, Inc.**

25 Main St., P.O. Box 328,

Denver, PA 17517

**E-MAIL** info@kalaswire.com

**P** 717 336 5575 **F** 717 335 1926