

Round Boat Cable

Construction:

Annealed bare or tinned stranded copper conductors insulated with PVC, twisted and jacketed with PVC to form a 105°C dry 75°C wet BC-5W2 600 Volt Mu lti-Conductor Boat Cable. UL Listed per UL 1426.

Size	Stranding	Insulation Thickness	Jacket Thickness	Nom O.D.	Std. Package	Shipping Weight ~lbs / 1000 feet**
18/2	16/.010"	.030"	.030"	0.302"	5500	36
18/3	16/.010"	.030"	.030"	0.309"	5000	47
18/4	16/.010"	.030"	.030"	0.338"	4000	59
16/2	26/.010"	.030"	.030"	0.315"	5000	45
16/3	26/.010"	.030"	.030"	0.335"	4500	59
16/4	26/.010"	.030"	.030"	0.367"	3500	75
14/2	41/.010"	.030"	.030"	0.351"	4000	60
14/3	41/.010"	.030"	.030"	0.374"	3500	80
14/4	41/.010"	.030"	.030"	0.411"	3000	103
14/5	41/.010"	.030"	.045"	0.485"	2500	138
12/2	65/.010"	.030"	.030"	0.382"	2500	77
12/3	65/.010"	.030"	.030"	0.407"	2500	106
12/4	65/.010"	.030"	.040"	0.468"	2000	145
12/5	65/.010"	.030"	.040"	0.515"	1500	175
10/2	104/.010"	.030"	.030"	0.435"	1500	109
10/3	104/.010"	.030"	.030"	0.465"	1500	153
10/4	104/.010"	.030"	.040"	0.540"	1000	208
10/5	104/.010"	.030"	.040"	0.584"	1000	255
8/3	133/.0112"	.045"	.060"	0.695"	1000	298
8/4	133/.0112"	.045"	.060"	0.768"	1000	380
8/5	133/.0112"	.045"	.060"	0.845"	1000	460
6/3	266/.010"	.060"	.060"	0.825"	500	430
6/4	266/.010"	.060"	.060"	0.910"	500	555
4/4	420/.010"	.060"	.070"	1.090"	500	825

- Special packaging is available upon request.
- UL Listed and ABYC compliant
- Oil resistant is optional
- **Polypropylene filler standard

MADE IN THE USA

Rev 1 6-9-2010

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926