

Flat Boat Cable

Construction:

Annealed bare or tinned stranded copper conductors PVC insulated and run parallel with a PVC jacket to form a 105°C dry 75°C wet BC-5W2 600 Volt Multi-Conductor Boat Cable. UL Listed per UL 1426.

Gauge	Stranding	Insulation Thickness	Jacket Thickness	Nom. OD Min. X Maj.	Std Package	Shipping Weight ~LB/1000'
18/2	16/.010"	0.030"	0.030"	0.180" X 0.280"	500 / 1000	34
16/2	26/.010"	0.030"	0.030"	0.192" X 0.311"	500 / 1000	41
16/3	26/.010"	0.030"	0.030"	0.187" X 0.433"	500 / 1000	60
14/2	41/.010"	0.030"	0.030"	0.215" X 0.350"	500 / 1000	55
14/3	41/.010"	0.030"	0.030"	0.220" X 0.487"	500 / 1000	82
12/2	65/.010"	0.030"	0.030"	0.230" X 0.381"	500 / 1000	75
12/3	65/.010"	0.030"	0.030"	0.230" X 0.528"	500 / 1000	110
10/2	104/.010"	0.030"	0.030"	0.250" X 0.430"	500 / 1000	108
10/3	104/.010"	0.030"	0.030"	0.270" X 0.620"	500 / 1000	158
8/2	7/19/.0112"	0.045"	0.045"	0.362" X 0.607"	500	182
8/3	7/19/.0112"	0.045"	0.045"	0.365" X 0.885"	500	265
6/2	7/38/.010"	0.060"	0.045"	0.425" X 0.740"	500	275
6/3	7/38/.010"	0.060"	0.045"	0.425" X 1.070"	500	407
4/2	7/60/.010"	0.060"	0.045"	0.494" X 0.901"	500	410

- Special packaging is available upon request.
- UL Listed & ABYC recognized
- Oil resistant is optional.

MADE IN THE USA

REV 01 7-12-2010

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926