

Single Conductor Boat Cable

Construction:

Annealed bare or tinned stranded copper conductor insulated with a high grade PVC.
UL listed, meets UL 1426 105°C dry 75°C wet BC-5W2 600 volts.

| Size | Stranding | Insulation Thickness | Nom O.D. | Std. Package | Shipping Weight ~lbs / 1000' |
|------|------------|----------------------|----------|--------------|------------------------------|
| 16 | 26/.010" | 0.030" | 0.123" | 30'000 drum | 14 |
| 14 | 41/.010" | 0.030" | 0.136" | 20,000 drum | 20 |
| 12 | 65/.010" | 0.030" | 0.156" | 18,000drum | 28 |
| 10 | 104/.010" | 0.030" | 0.181" | 12,000 drum | 43 |
| 8 | 168/.010" | 0.045" | 0.256" | 1,000 | 70 |
| 6 | 266/.010" | 0.060" | 0.320" | 1,000 | 114 |
| 4 | 420/.010" | 0.060" | 0.386" | 1,000 | 175 |
| 2 | 665/.010" | 0.060" | 0.446" | 500 | 254 |
| 1 | 836/.010" | 0.080" | 0.520" | 500 | 336 |
| 1/0 | 1064/.010" | 0.080" | 0.575" | 500 | 407 |
| 2/0 | 1330/.010" | 0.080" | 0.625" | 500 | 505 |
| 3/0 | 1672/.010" | 0.080" | 0.670" | 500 | 619 |
| 4/0 | 2109/.010" | 0.080" | 0.740" | 500 | 767 |

- Special stranding and packaging available upon request.
- UL Listed
- ABYC

MADE IN THE USA

Rev 1 6-9-2010

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926